



**AMAZON**<sup>®</sup>  
LUBRICANTS

***HIGH RACING***

**PRODUCT CATALOGUE**

# About Us

Amazon Lubricants: A Beacon of Innovation and Sustainability in the Lubricants Industry in the dynamic world of lubricants, Amazon Lubricants stands tall as a beacon of innovation and sustainability. Founded in 2018, our company has swiftly established itself as a leading manufacturer and exporter of high-quality industrial lubricants, catering to a global clientele across MENA, CIS, Africa, and beyond.

At the heart of our success lies an unwavering commitment to cutting-edge research and development. Our state-of-the-art laboratory, staffed by a team of brilliant minds, continuously explores new frontiers in lubricant technology. This relentless pursuit of innovation has led to the development of a comprehensive range of lubricants that meet the ever-evolving needs of our customers.

Our commitment extends beyond innovation to encompass sustainability. We recognize the profound impact our industry has on the environment, and we are dedicated to minimizing our footprint. Our manufacturing processes adhere to the strictest environmental standards, and we actively seek ways to reduce waste and promote circularity.

Amazon Lubricants is not merely a manufacturer of lubricants; we are a trusted partner to our customers. We understand the unique challenges they face and tailor our solutions to address their specific needs. Our team of dedicated professionals is always available to provide expert advice and support, ensuring that our customers can operate smoothly and efficiently.

As we look towards the future, Amazon Lubricants remains steadfast in its pursuit of excellence. We are committed to

## **Innovation and Development**

Relentlessly innovating and developing world-class lubricants that empower businesses and societies to operate efficiently, responsibly, and sustainably.

## **Highest Standard of Quality**

Upholding the highest standards of quality and precision in our manufacturing processes, ensuring the consistent production of exceptional lubricants.

## **Collaboration**

Collaborating with our customers and partners to drive innovation and sustainability across the lubricants industry.



PLANT :  
New Industrial Area, UAQ, UAE  
Ph: 00971 54 7047811

[info@amazonlubricants.com](mailto:info@amazonlubricants.com)  
[www.amazonlubricants.com](http://www.amazonlubricants.com)



MAIN OFFICE:  
Suite 1, Cochrane House , Admirals Way,  
Isle Of Dogs,  
London E14 9ud, United Kingdom  
+44 203 719 0255  
+44 79 49 439 459

# Approval & Certificates

The image displays four SAE License Agreements (SCHEDULE A - LICENSE AGREEMENT) issued by API Engines and SAE International. Each agreement is for a different engine model:
 

- 1. **AMAZON SUPER PLUS SAE 20W-50 API CH-4/SJ**: Lists various engine models including AMZ01-001, AMZ01-002, etc.
- 2. **AMAZON SUPER PLUS SAE 15W-40 API CH-4/SJ**: Lists various engine models including AMZ01-001, AMZ01-002, etc.
- 3. **AMAZON SUPER PLUS SAE 15W-40 API CH-4/SJ**: Lists various engine models including AMZ01-001, AMZ01-002, etc.
- 4. **AMAZON SUPER PLUS SAE 15W-40 API CH-4/SJ**: Lists various engine models including AMZ01-001, AMZ01-002, etc.

 Each agreement includes a table of engine models and their corresponding SAE grades, along with the API and SAE logos and a signature line.

**Certificate of Registration**  
Awarded to  
**AMAZON LUBRICANTS AND GREASE L.L.C**  
at  
P.O. BOX NO. 343133, NEW INDUSTRIAL AREA, UMM AL QUWAIN, UAE

Quality Registrar Systems certify that the management system of the above organization has been audited and found to be in compliance with the QRS requirements for registration of the management system standard detailed below:

**ISO 45001:2018**  
Occupational Health and Safety Management Systems  
Scope of work  
MANUFACTURING OF LUBRICANTS & GREASE

QAF 10  
Certificate No: AMU13005  
Originally Registered: 16 FEB 2019  
Latest Issue: 05 MAR 2022  
Valid up to: 15 FEB 2025

MANAGING OFFICE ADDRESS:  
QRS (QAF 10)  
P.O. Box 343133  
Umm Al Quwain, UAE  
Tel: +971 2 471 2148  
Fax: +971 2 471 1448  
www.qrs.com

**Certificate of Registration**  
Awarded to  
**AMAZON LUBRICANTS AND GREASE L.L.C**  
at  
P.O. BOX NO. 343133, NEW INDUSTRIAL AREA, UMM AL QUWAIN, UAE

Quality Registrar Systems certify that the management system of the above organization has been audited and found to be in compliance with the QRS requirements for registration of the management system standard detailed below:

**ISO 9001:2015**  
Quality Management Systems  
Scope of work  
MANUFACTURING OF LUBRICANTS & GREASE

QAF 30  
Certificate No: AMU13022  
Originally Registered: 16 FEB 2019  
Latest Issue: 05 MAR 2022  
Valid up to: 15 FEB 2025

MANAGING OFFICE ADDRESS:  
QRS (QAF 30)  
P.O. Box 343133  
Umm Al Quwain, UAE  
Tel: +971 2 471 2148  
Fax: +971 2 471 1448  
www.qrs.com

**Certificate of Registration**  
Awarded to  
**AMAZON LUBRICANTS AND GREASE L.L.C**  
at  
P.O. BOX NO. 343133, NEW INDUSTRIAL AREA, UMM AL QUWAIN, UAE

Quality Registrar Systems certify that the management system of the above organization has been audited and found to be in compliance with the QRS requirements for registration of the management system standard detailed below:

**ISO 14001:2015**  
Environmental Management Systems  
Scope of work  
MANUFACTURING OF LUBRICANTS & GREASE

QAF 10  
Certificate No: AMU13005  
Originally Registered: 16 FEB 2019  
Latest Issue: 05 MAR 2022  
Valid up to: 15 FEB 2025

MANAGING OFFICE ADDRESS:  
QRS (QAF 10)  
P.O. Box 343133  
Umm Al Quwain, UAE  
Tel: +971 2 471 2148  
Fax: +971 2 471 1448  
www.qrs.com

**Statement of Quality**  
**AMAZON SUPER PLUS SAE 20W-50 API CH-4/SJ**

We hereby confirm that **AMAZON SUPER PLUS SAE 20W-50 API CH-4/SJ** engine oil formulated and blended with Afton Chemical US additive package **HTCC™ 1200W** at 8.7% mass of code **LSB 20509** meets the performance of:

Caterpillar ECF-1a

This statement is invalidated if the formulation and/or recommended blending procedures have been changed.

For Afton Chemical Ltd,  
*P.P. E Toprak*  
Evelina Toprak  
Customer Technical Service Technologist  
January 2020

Afton Chemical Ltd  
10000 Westchester Avenue, 91720, CA, USA  
Tel: +1 949 234 1111 Fax: +1 949 234 1112  
www.aftonchemical.com

**Statement of Quality**  
**AMAZON SUPER PLUS SAE 15W-40 API CH-4/SJ**

We hereby confirm that **AMAZON SUPER PLUS SAE 15W-40 API CH-4/SJ** engine oil formulated and blended with Afton Chemical US additive package **HTCC™ 1200W** at 8.7% mass of code **LSB 15215-0** meets the performance of:

M 3275-1  
Caterpillar ECF-1a

This statement is invalidated if the formulation and/or recommended blending procedures have been changed.

For Afton Chemical Ltd,  
*P.P. E Toprak*  
Evelina Toprak  
Customer Technical Service Technologist  
January 2020

Afton Chemical Ltd  
10000 Westchester Avenue, 91720, CA, USA  
Tel: +1 949 234 1111 Fax: +1 949 234 1112  
www.aftonchemical.com

**Statement of Quality**  
**AMAZON SUPER PLUS SAE 15W-40 API CH-4/SJ**

We hereby confirm that **AMAZON SUPER PLUS SAE 15W-40 API CH-4/SJ** engine oil formulated and blended with Afton Chemical US additive package **HTCC™ 1200W** at 8.7% mass of code **LSB 15215-0** meets the performance of:

M 3275-1  
Caterpillar ECF-1a

This statement is invalidated if the formulation and/or recommended blending procedures have been changed.

For Afton Chemical Ltd,  
*P.P. E Toprak*  
Evelina Toprak  
Customer Technical Service Technologist  
January 2020

Afton Chemical Ltd  
10000 Westchester Avenue, 91720, CA, USA  
Tel: +1 949 234 1111 Fax: +1 949 234 1112  
www.aftonchemical.com







**HIGH RACING  
GASOLINE  
ENGINE OIL**

EXTREME  
PERFORMANCE

  
**AMAZON**  
LUBRICANTS





**PRODUCT DESCRIPTION:**

SAE 0W-16 API SP is advanced high performance fully synthetic engine oil designed to help deliver outstanding engine protection and enhanced fuel economy. SAE 0W-16 meets and exceeds the requirements of various vehicle manufacturer and industry standard and out performs conventional oils.

**MEETS OR EXCEEDS:** API SP, ILSAC GF-6B

## HIGH RACING SAE 0W-16 SP

TECHNICAL DATA			
S. No.	DESCRIPTION	METHOD	TYPICAL RESULTS
<b>SAE 0W-16</b>			
1	Appearance	Visual	Clear & Bright
2	Color	D 1500	L2.0
3	Kinematic, Viscosity mm <sup>2</sup> /s @ 40°C	D 445	42.0
4	Kinematic, Viscosity mm <sup>2</sup> /s @ 100°C	D 445	8.25
5	Viscosity Index	D 2270	176
6	Flash Point ,COC, °C	D 92	216
7	Pour Point, °C	D 97	-42
8	TBN mg/KOH/g	D 2896	7.5

AVAILABLE PACKS  
1L, 4L, 5L, 20L, 25L, 208L Bulk



**PRODUCT DESCRIPTION:**

SAE 0W-20 API SP is advanced high performance fully synthetic engine oil designed to help deliver outstanding engine protection and enhanced fuel economy. SAE 0W-20 meets and exceeds the requirements of various vehicle manufacturer and industry standard and out performs conventional oils.

**MEETS OR EXCEEDS:** API SP, ILSAC GF-6A, FORD WSS-M2C962-A/WSS-M2C947-B1, DEXOS1™ Gen3,

## HIGH RACING SAE 0W-20 SP

TECHNICAL DATA			
S. No.	DESCRIPTION	METHOD	TYPICAL RESULTS
<b>SAE 0W-20</b>			
1	Appearance	Visual	Clear & Bright
2	Color	D 1500	L2.0
3	Kinematic, Viscosity mm <sup>2</sup> /s @ 40°C	D 445	46.5
4	Kinematic, Viscosity mm <sup>2</sup> /s @ 100°C	D 445	8.8
5	Viscosity Index	D 2270	172
6	Flash Point ,COC, °C	D 92	216
7	Pour Point, °C	D 97	-42
8	TBN mg/KOH/g	D 2896	7.5

AVAILABLE PACKS  
1L, 4L, 5L, 20L, 25L, 208L Bulk



**PRODUCT DESCRIPTION:**

SAE 0W-30 API SP is advanced high performance fully synthetic engine oil designed to help deliver outstanding engine protection and enhanced fuel economy. SAE 0W-30 meets and exceeds the requirements of various vehicle manufacturer and industry standard and out performs conventional oils.

**MEETS OR EXCEEDS:** API SP, ILSAC GF-6A, FORD WSS-M2C960-A/WSS-M2C945-B1, DEXOS1™ GEN3, CHRYSLER MS6395

## HIGH RACING SAE 0W-30 SP

TECHNICAL DATA			
S. No.	DESCRIPTION	METHOD	TYPICAL RESULTS
<b>SAE 0W-30</b>			
1	Appearance	Visual	Clear & Bright
2	Color	D 1500	L2.0
3	Kinematic, Viscosity mm <sup>2</sup> /s @ 40°C	D 445	65.1
4	Kinematic, Viscosity mm <sup>2</sup> /s @ 100°C	D 445	11.6
5	Viscosity Index	D 2270	175
6	Flash Point ,COC, °C	D 92	220
7	Pour Point, °C	D 97	-45
8	TBN mg/KOH/g	D 2896	8.0

AVAILABLE PACKS  
1L, 4L, 5L, 20L, 25L, 208L Bulk



# HIGH RACING GASOLINE ENGINE OIL



## HIGH RACING SAE 0W-40 SP

TECHNICAL DATA			
S. No.	DESCRIPTION	METHOD	TYPICAL RESULTS
<b>SAE 0W-40</b>			
1	Appearance	Visual	Clear & Bright
2	Color	D 1500	L2.0
3	Kinematic, Viscosity mm <sup>2</sup> /s @ 40°C	D 445	92.5
4	Kinematic, Viscosity mm <sup>2</sup> /s @ 100°C	D 445	15.2
5	Viscosity Index	D 2270	174
6	Flash Point ,COC,°C	D 92	222
7	Pour Point, °C	D 97	-42
8	TBN mg/KOH/g	D 2896	8.1

AVAILABLE PACKS  
1L, 4L, 5L, 20L, 25L, 208L, Bulk

### PRODUCT DESCRIPTION:

**SAE 0W-40 API SP** is advanced high performance fully synthetic engine oil designed to help deliver outstanding engine protection and enhanced fuel economy. SAE 0W-40 meets and exceeds the requirements of various vehicle manufacturer and industry standard and out performs conventional oils.

**MEETS OR EXCEEDS:** API SP, ACEA A3/B4, MB 229.3, MB 229.5, PORSCHE A40, VW 502.00/505.00.



## HIGH RACING SAE 5W-20 SP

TECHNICAL DATA			
S. No.	DESCRIPTION	METHOD	TYPICAL RESULTS
<b>SAE 5W-20</b>			
1	Appearance	Visual	Clear & Bright
2	Color	D 1500	L2.0
3	Kinematic, Viscosity mm <sup>2</sup> /s @ 40°C	D 445	47.9
4	Kinematic, Viscosity mm <sup>2</sup> /s @ 100°C	D 445	8.95
5	Viscosity Index	D 2270	165
6	Flash Point ,COC,°C	D 92	216
7	Pour Point, °C	D 97	-42
8	TBN mg/KOH/g	D 2896	7.6

AVAILABLE PACKS  
1L, 4L, 5L, 20L, 25L, 208L, Bulk

### PRODUCT DESCRIPTION:

**SAE 5W-20 API SP** is advanced high performance fully synthetic engine oil designed to help deliver outstanding engine protection and enhanced fuel economy. SAE 5W-20 meets and exceeds the requirements of various vehicle manufacturer and industry standard and out performs conventional oils.

**MEETS OR EXCEEDS:** API SP, ILSAC GF-6A, FORD WSS-M2C960-A/WSS-M2C945-B1, DEXOS1™ Gen3, CHRYSLER Ms6395



## HIGH RACING SAE 5W-30 SP

TECHNICAL DATA			
S. No.	DESCRIPTION	METHOD	TYPICAL RESULTS
<b>SAE 5W-30</b>			
1	Appearance	Visual	Clear & Bright
2	Color	D 1500	L2.0
3	Kinematic, Viscosity mm <sup>2</sup> /s @ 40°C	D 445	75.9
4	Kinematic, Viscosity mm <sup>2</sup> /s @ 100°C	D 445	12.1
5	Viscosity Index	D 2270	156
6	Flash Point ,COC,°C	D 92	220
7	Pour Point, °C	D 97	-27
8	TBN mg/KOH/g	D 2896	8.1

AVAILABLE PACKS  
1L, 4L, 5L, 20L, 25L, 208L, Bulk

### PRODUCT DESCRIPTION:

**SAE 5W-30 API SP** is advanced high performance fully synthetic engine oil designed to help deliver outstanding engine protection and enhanced fuel economy. SAE 5W-30 meets and exceeds the requirements of various vehicle manufacturer and industry standard and out performs conventional oils.

**MEETS OR EXCEEDS:** API SP, ILSAC GF-6A, FORD WSS-M2C961-A/WSS-M2C946-B1, DEXOS1™ GEN3, CHRYSLER MS6395







## HIGH RACING SAE 5W-40 SP

TECHNICAL DATA			
S. No.	DESCRIPTION	METHOD	TYPICAL RESULTS
<b>SAE 5W-40</b>			
1	Appearance	Visual	Clear & Bright
2	Color	D 1500	L2.0
3	Kinematic, Viscosity mm <sup>2</sup> /s @ 40°C	D 445	86.8
4	Kinematic, Viscosity mm <sup>2</sup> /s @ 100°C	D 445	14.1
5	Viscosity Index	D 2270	168
6	Flash Point ,COC, °C	D 92	220
7	Pour Point, °C	D 97	-42
8	TBN mg/KOH/g	D 2896	7.6

AVAILABLE PACKS  
1L, 4L, 5L, 20L, 25L, 208L Bulk



### PRODUCT DESCRIPTION:

**SAE 5W-40 API SP** is advanced high performance fully synthetic engine oil designed to help deliver outstanding engine protection and enhanced fuel economy. **SAE 5W-40** meets and exceeds the requirements of various vehicle manufacturer and industry standard and out performs conventional oils.

**MEETS OR EXCEEDS:** API SP, ACEA A3/B4, MB 229.5, PORCSHE A40, VW 502.00/505.00, RENAULT RN 0700/0710



## HIGH RACING SAE 0W-16 SN

TECHNICAL DATA			
S. No.	DESCRIPTION	METHOD	TYPICAL RESULTS
<b>SAE 0W-16</b>			
1	Appearance	Visual	Clear & Bright
2	Color	D 1500	L2.0
3	Kinematic, Viscosity mm <sup>2</sup> /s @ 40°C	D 445	41.6
4	Kinematic, Viscosity mm <sup>2</sup> /s @ 100°C	D 445	8.1
5	Viscosity Index	D 2270	172
6	Flash Point ,COC, °C	D 92	216
7	Pour Point, °C	D 97	-45
8	TBN mg/KOH/g	D 2896	7.2

AVAILABLE PACKS  
1L, 4L, 5L, 20L, 25L, 208L Bulk



### PRODUCT DESCRIPTION:

**SAE 0W-16 API SN** is advanced high performance fully synthetic motor oil designed to help deliver outstanding engine protection and enhanced fuel economy. **SAE 0W-16** viscosity grade oils are commonly recommended for use in many new vehicles with modern engine technology to help maximize engine performance and provide horse power protection.

**MEETS OR EXCEEDS:** API SN, ILSAC GF-5, FORD WSS-M2C-947A, DEXOS1™, GMW16076/16182



## HIGH RACING SAE 0W-20 SN

TECHNICAL DATA			
S. No.	DESCRIPTION	METHOD	TYPICAL RESULTS
<b>SAE 0W-20</b>			
1	Appearance	Visual	Clear & Bright
2	Color	D 1500	L2.0
3	Kinematic, Viscosity mm <sup>2</sup> /s @ 40°C	D 445	43.0
4	Kinematic, Viscosity mm <sup>2</sup> /s @ 100°C	D 445	8.3
5	Viscosity Index	D 2270	172
6	Flash Point ,COC, °C	D 92	216
7	Pour Point, °C	D 97	-45
8	TBN mg/KOH/g	D 2896	7.6

AVAILABLE PACKS  
1L, 4L, 5L, 20L, 25L, 208L Bulk



### PRODUCT DESCRIPTION:

**SAE 0W-20 API SN** is advanced high performance fully synthetic motor oil designed to help deliver outstanding engine protection and enhanced fuel economy. **SAE 0W-20** viscosity grade oils are commonly recommended for use in many new vehicles with modern engine technology to help maximize engine performance and provide horse power protection.

**MEETS OR EXCEEDS:** API SN, ILSAC GF-5, FORD WSS-M2C-947A, DEXOS1™, GMW16076/16182





## HIGH RACING SAE 0W-30 SN

TECHNICAL DATA			
S. No.	DESCRIPTION	METHOD	TYPICAL RESULTS
<b>SAE 0W-30</b>			
1	Appearance	Visual	Clear & Bright
2	Color	D 1500	L2.0
3	Kinematic, Viscosity mm <sup>2</sup> /s @ 40°C	D 445	65.5
4	Kinematic, Viscosity mm <sup>2</sup> /s @ 100°C	D 445	11.7
5	Viscosity Index	D 2270	176
6	Flash Point ,COC, °C	D 92	220
7	Pour Point, °C	D 97	-42
8	TBN mg/KOH/g	D 2896	7.5

AVAILABLE PACKS  
1L, 4L, 5L, 20L, 25L, 208L Bulk



### PRODUCT DESCRIPTION:

**SAE 0W-30 API SN** is advanced high performance fully synthetic motor oil designed to help deliver outstanding engine protection and enhanced fuel economy. **SAE 0W-30** viscosity grade oils are commonly recommended for use in many new vehicles with modern engine technology to help maximize engine performance and provide horse power protection.

**MEETS OR EXCEEDS:** API SN, ILSAC GF-5, FORD WSS-M2C-947A, DEXOS1™, GMW16076/16182



## HIGH RACING SAE 0W-40 SN

TECHNICAL DATA			
S. No.	DESCRIPTION	METHOD	TYPICAL RESULTS
<b>SAE 0W-40</b>			
1	Appearance	Visual	Clear & Bright
2	Color	D 1500	L1.5
3	Kinematic, Viscosity mm <sup>2</sup> /s @ 40°C	D 445	86.5
4	Kinematic, Viscosity mm <sup>2</sup> /s @ 100°C	D 445	14.5
5	Viscosity Index	D 2270	175
6	Flash Point ,COC, °C	D 92	228
7	Pour Point, °C	D 97	-42
8	TBN mg/KOH/g	D 2896	7.6

AVAILABLE PACKS  
1L, 4L, 5L, 20L, 25L, 208L Bulk



### PRODUCT DESCRIPTION:

**SAE 0W-40 API SN** is advanced high performance fully synthetic motor oil designed to help deliver outstanding engine protection and enhanced fuel economy. **SAE 0W-40** viscosity grade oils are commonly recommended for use in many new vehicles with modern engine technology to help maximize engine performance and provide horse power protection.

**MEETS OR EXCEEDS:** API SN, ILSAC GF-5, FORD WSS-M2C-947A, DEXOS1™, GMW16076/16182



## HIGH RACING SAE 5W-20 SN

TECHNICAL DATA			
S. No.	DESCRIPTION	METHOD	TYPICAL RESULTS
<b>SAE 5W-20</b>			
1	Appearance	Visual	Clear & Bright
2	Color	D 1500	L2.0
3	Kinematic, Viscosity mm <sup>2</sup> /s @ 40°C	D 445	46.3
4	Kinematic, Viscosity mm <sup>2</sup> /s @ 100°C	D 445	8.8
5	Viscosity Index	D 2270	165
6	Flash Point ,COC, °C	D 92	216
7	Pour Point, °C	D 97	-42
8	TBN mg/KOH/g	D 2896	7.5

AVAILABLE PACKS  
1L, 4L, 5L, 20L, 25L, 208L Bulk



### PRODUCT DESCRIPTION:

**SAE 5W-20 API SN** is advanced high performance fully synthetic motor oil designed to help deliver outstanding engine protection and enhanced fuel economy. **SAE 5W-20** viscosity grade oils are commonly recommended for use in many new vehicles with modern engine technology to help maximize engine performance and provide horse power protection.

**MEETS OR EXCEEDS:** API SN, ILSAC GF-5, FORD WSS-M2C-945A, DEXOS1™, GMW16096/16182



## HIGH RACING SAE 5W-30 SN

TECHNICAL DATA			
S. No.	DESCRIPTION	METHOD	TYPICAL RESULTS
<b>SAE 5W-30</b>			
1	Appearance	Visual	Clear & Bright
2	Color	D 1500	L2.0
3	Kinematic, Viscosity mm <sup>2</sup> /s @ 40°C	D 445	69
4	Kinematic, Viscosity mm <sup>2</sup> /s @ 100°C	D 445	11.8
5	Viscosity Index	D 2270	165
6	Flash Point ,COC, °C	D 92	220
7	Pour Point, °C	D 97	-39
8	TBN mg/KOH/g	D 2896	7.0

AVAILABLE PACKS  
1L, 4L, 5L, 20L, 25L, 208L, Bulk

### PRODUCT DESCRIPTION:

**SAE 5W-30 API SN** is advanced high performance fully synthetic motor oil designed to help deliver outstanding engine protection and enhanced fuel economy. **SAE 5W-30** viscosity grade oils are commonly recommended for use in many new vehicles with modern engine technology to help maximize engine performance and provide horse power protection.

**MEETS OR EXCEEDS:** API SN, ILSAC GF-5, FORD WSS-M2C-946A, DEXOS1™, GMW 16181, GMW15827



## HIGH RACING SAE 5W-40 SN

TECHNICAL DATA			
S. No.	DESCRIPTION	METHOD	TYPICAL RESULTS
<b>SAE 5W-40</b>			
1	Appearance	Visual	Clear & Bright
2	Color	D 1500	L2.0
3	Kinematic, Viscosity mm <sup>2</sup> /s @ 40°C	D 445	84
4	Kinematic, Viscosity mm <sup>2</sup> /s @ 100°C	D 445	13.5
5	Viscosity Index	D 2270	168
6	Flash Point ,COC, °C	D 92	230
7	Pour Point, °C	D 97	-42
8	TBN mg/KOH/g	D 2896	7.3

AVAILABLE PACKS  
1L, 4L, 5L, 20L, 25L, 208L, Bulk

### PRODUCT DESCRIPTION:

**SAE 5W-40 API SN** is advanced high performance fully synthetic motor oil designed to help deliver outstanding engine protection and enhanced fuel economy. **SAE 5W-40** viscosity grade oils are commonly recommended for use in many new vehicles with modern engine technology to help maximize engine performance and provide horse power protection.

**MEETS OR EXCEEDS:** API SN, ILSAC GF-5, ACEA A3/B4-16, MB229.3, MB229.5, PORSCHE A40, VW 502.00/505.00, RENAULT RN 0710/0700, GM-LL-B-025, BMW LL-01



## HIGH RACING SAE 10W-30 SN

TECHNICAL DATA			
S. No.	DESCRIPTION	METHOD	TYPICAL RESULTS
<b>SAE 10W-30</b>			
1	Appearance	Visual	Clear & Bright
2	Color	D 1500	L2.5
3	Kinematic, Viscosity mm <sup>2</sup> /s @ 40°C	D 445	76
4	Kinematic, Viscosity mm <sup>2</sup> /s @ 100°C	D 445	11.9
5	Viscosity Index	D 2270	152
6	Flash Point ,COC, °C	D 92	228
7	Pour Point, °C	D 97	-36
8	TBN mg/KOH/g	D 2896	7.2

AVAILABLE PACKS  
1L, 4L, 5L, 20L, 25L, 208L, Bulk

### PRODUCT DESCRIPTION:

**SAE 10W-30 API SN** is advanced high performance fully synthetic motor oil designed to help deliver outstanding engine protection and enhanced fuel economy. **SAE 10W-30** viscosity grade oils are commonly recommended for use in many new vehicles with modern engine technology to help maximize engine performance and provide horse power protection.

**MEETS OR EXCEEDS:** API SN, ILSAC GF-5, CHRYSLER MS-6395





# HIGH RACING GASOLINE ENGINE OIL



## HIGH RACING SAE 10W-40 SN

TECHNICAL DATA			
S. No.	DESCRIPTION	METHOD	TYPICAL RESULTS
<b>SAE 10W-40</b>			
1	Appearance	Visual	Clear & Bright
2	Color	D 1500	L2.0
3	Kinematic, Viscosity mm <sup>2</sup> /s @ 40°C	D 445	101
4	Kinematic, Viscosity mm <sup>2</sup> /s @ 100°C	D 445	15.2
5	Viscosity Index	D 2270	151
6	Flash Point ,COC, °C	D 92	220
7	Pour Point, °C	D 97	-36
8	TBN mg/KOH/g	D 2896	7.6

AVAILABLE PACKS  
1L, 4L, 5L, 20L, 25L, 208L Bulk

### PRODUCT DESCRIPTION:

SAE 10W-40 API SN is advanced high performance fully synthetic motor oil designed to help deliver outstanding engine protection and enhanced fuel economy. SAE 10W-40 viscosity grade oils are commonly recommended for use in many new vehicles with modern engine technology to help maximize engine performance and provide horse power protection.

**MEETS OR EXCEEDS:** API SN, ACEAA3/B4-16, MB229.3, RENAULT RN 0710/0700, PSA B71 2300, ACEAA3/B3-16, MB 229.1



## HIGH RACING SAE 10W-50 SN

TECHNICAL DATA			
S. No.	DESCRIPTION	METHOD	TYPICAL RESULTS
<b>SAE 10W-50</b>			
1	Appearance	Visual	Clear & Bright
2	Color	D 1500	L2.0
3	Kinematic, Viscosity mm <sup>2</sup> /s @ 40°C	D 445	80
4	Kinematic, Viscosity mm <sup>2</sup> /s @ 100°C	D 445	12.1
5	Viscosity Index	D 2270	165
6	Flash Point ,COC, °C	D 92	222
7	Pour Point, °C	D 97	-36
8	TBN mg/KOH/g	D 2896	7.6

AVAILABLE PACKS  
1L, 4L, 5L, 20L, 25L, 208L Bulk

### PRODUCT DESCRIPTION:

SAE 10W-50 API SN is advanced high performance fully synthetic motor oil designed to help deliver outstanding engine protection and enhanced fuel economy. SAE 10W-50 viscosity grade oils are commonly recommended for use in many new vehicles with modern engine technology to help maximize engine performance and provide horse power protection.

**MEETS OR EXCEEDS:** API SN, ACEAA3/B4-16, MB229.3, RENAULT RN 0710/0700, PSA B71 2300, ACEAA3/B3-16, MB 229.1



## HIGH RACING SAE 10W-60 SN

TECHNICAL DATA			
S. No.	DESCRIPTION	METHOD	TYPICAL RESULTS
<b>SAE 10W-60</b>			
1	Appearance	Visual	Clear & Bright
2	Color	D 1500	L2.5
3	Kinematic, Viscosity mm <sup>2</sup> /s @ 40°C	D 445	196
4	Kinematic, Viscosity mm <sup>2</sup> /s @ 100°C	D 445	22.5
5	Viscosity Index	D 2270	139
6	Flash Point ,COC, °C	D 92	226
7	Pour Point, °C	D 97	-36
8	TBN mg/KOH/g	D 2896	7.2

AVAILABLE PACKS  
1L, 4L, 5L, 20L, 25L, 208L Bulk

### PRODUCT DESCRIPTION:

SAE 10W-60 API SN is advanced high performance fully synthetic motor oil designed to help deliver outstanding engine protection and enhanced fuel economy. SAE 10W-60 viscosity grade oils are commonly recommended for use in many new vehicles with modern engine technology to help maximize engine performance and provide horse power protection.

**MEETS OR EXCEEDS:** API SN, ACEAA3/B4-16, MB229.3, RENAULT RN 0710/0700, PSA B71 2300, ACEAA3/B3-16, MB 229.1





